

KBA 44 v2



Oil Pattern Distance 44 **Forward Oil Total** 18.05 mL **Tank Configuration** N/A

Reverse Brush Drop Reverse Oil Total Tank A Conditioner

36 8.15 mL Kegel Oil Per Board **Volume Oil Total Tank B Conditioner**

50 ul 26.2 mL Kegel

1 2L 2R 4 18 A 148 0.0 7.6 7.6 7400 2 6L 6R 1 18 A 29 7.6 10.1 2.5 1450 3 7L 7R 2 18 A 54 10.1 15.2 5.1 2700 4 8L 8R 2 18 A 50 15.2 20.3 5.1 2500 5 10L 10R 2 18 A 42 20.3 25.4 5.1 2100 6 11L 11R 2 22 A 38 25.4 31.6 6.2 1900 7 2L 2R 0 26 A 0 31.6 44.0 12.4 0		START	STOP	LOADS	SPEED	TANK	CROSSED	START	END	FEET	T.OIL
3 7L 7R 2 18 A 54 10.1 15.2 5.1 2700 4 8L 8R 2 18 A 50 15.2 20.3 5.1 2500 5 10L 10R 2 18 A 42 20.3 25.4 5.1 2100 6 11L 11R 2 22 A 38 25.4 31.6 6.2 1900	1	2L	2R	4	18	Α	148	0.0	7.6	7.6	7400
4 8L 8R 2 18 A 50 15.2 20.3 5.1 2500 5 10L 10R 2 18 A 42 20.3 25.4 5.1 2100 6 11L 11R 2 22 A 38 25.4 31.6 6.2 1900	2	6L	6R	1	18	Α	29	7.6	10.1	2.5	1450
5 10L 10R 2 18 A 42 20.3 25.4 5.1 2100 6 11L 11R 2 22 A 38 25.4 31.6 6.2 1900	3	7L	7R	2	18	Α	54	10.1	15.2	5.1	2700
6 11L 11R 2 22 A 38 25.4 31.6 6.2 1900	4	8L	8R	2	18	Α	50	15.2	20.3	5.1	2500
	5	10L	10R	2	18	Α	42	20.3	25.4	5.1	2100
7 2L 2R 0 26 A 0 31.6 44.0 12.4 0	6	11L	11R	2	22	Α	38	25.4	31.6	6.2	1900
	7	2L	2R	0	26	Α	0	31.6	44.0	12.4	0

	START	STOP	LOADS	SPEED	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	30	В	0	44.0	27.0	-17.0	0
2	12L	10R	2	22	В	38	27.0	20.8	-6.2	1900
3	11L	9R	2	18	В	42	20.8	15.7	-5.1	2100
4	10L	8R	2	18	В	46	15.7	10.6	-5.1	2300
5	2L	2R	1	14	В	37	10.6	8.7	-1.9	1850
6	2L	2R	0	14	В	0	8.7	0.0	-8.7	0

Cleaner Ratio Main Mix Cleaner Ratio Back End Mix Cleaner Ratio Back End Distance Buffer RPM: 4 = 700 | 3 = 500 | 2 = 200 | 1 = 100

NA NA NA Forward Reverse Combined



				<u> </u>		
ltem	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Mlddle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	3.45	1.39	1	1	1.19	3.45



